



Venture Tape

30 Commerce Road
Rockland, MA 02370-0384

9/23/2008
781-871-1400
Fax: 781-871-0065

1562CW-R

POLYPROPYLENE FACING TAPE

DESCRIPTION: A 4x4 bidirectional, UL listed, reinforced white polypropylene/ scrim/foil lamination coated with a special cold weather acrylic pressure sensitive system. This adhesive system combines superior quick stick at normal temperatures with superior low temperature performance.

APPLICATIONS: Primarily used to seal the seams of grease duct firewraps.

TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
Thickness: <i>(exclusive of liner)</i>	10.5 mils	262 micron
Adhesion:		
Peel (PSTC#1)	68 oz/inch width	19.25 N/2.5cm
Shear (PSTC#7)15+ hrs @	2.2psi	15.2 kPa
Tensile:	40 lbs/inch width	181 N/2.5 cm
Standard Widths:	2", 3", 4", 5"	5.1cm, 7.6cm, 10.2cm and 12.7cm
Standard Length:	50 yards	46 meters
Core:	3 inches	7.6 cm

IMPORTANT INFORMATION:

The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using the product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.
12/06/02